



SHBD1K

- Magnetic B-Field Sensor Head
- Isotropic
- DC–1000Hz
- >80dB dynamic range
- Sensitivity >1mT

Features

The SHBD1K B-field sensor head is based on a set of three orthogonally arranged Hall sensors. The three voltages which correspond to the spatial components are individually available at the sensor head output. An SM-series meter (required for use of this sensor head) calculates the resulting isotropic field strength.



The characteristics of this sensor head comply with the requirements for instruments measuring human exposure to magnetic fields as required by law in both public and professional environments.

This sensor head detects magnetic fields from 0 Hz to 1000 Hz which typically occur in broadcasting, telecoms, ISM and industry. This sensor head is recommended for measuring human exposure to magnetic fields in the following environments: MRI-imaging, industrial electrolysis and electroplating, power supply plants for railway stations.

The sensor head is supplied with factory calibration. This model is also available in an M1-version which includes an accredited 17025-compliant calibration.

Typical Applications

- MRI-Magnetic Resonance Imaging
- Industrial Electrolysis and Electroplating
- Railway: Power Supply Plants

Specifications

Frequency Range: 0 Hz–1000 Hz

Type of Frequency Response: Flat

Measurement Range: 1 mT–15 T

Dynamic Range: >80 dB

Sensor Type: Hall sensors

Directivity: Isotropic

Accuracy:

Flatness Frequency Response:
 ± 0.5 dB (0 Hz–1 kHz)@ 5mT

Linearity: ± 0.7 dB (5–100 mT)

Isotropic Response (@ 10mT): ± 0.5 dB

Operation Temperature: 0°C–40°C

Size: 278 x 16 mm, 10.95 x 0.63 in

Weight: 63g, 2.23oz

Export Classification: EAR99

AR RF/Microwave
Instrumentation
160 School House Rd
Souderton, PA 18964
215-723-8181

For an applications engineer call: 800.933.8181

www.arworld.us

To order AR Products, call 215.723.8181. For an applications engineer call: 800.933.8181. Direct to Service call: 215.723.0275 or email: service@arworld.us For Faxing Orders: 866.859.0582 (Orders Only Please) info@arworld.us

Approved for public release by AR RF/Microwave Instrumentation

111615