

SOL8SDR-M

BluCore OEM Software Defined Radio Module

Overview:

DTC's BluCore OEM is a ruggedized, miniature Software Defined Radio transceiver, designed specifically for size and weight critical UxV applications and is particularly suitable for small drone platforms. Based around DTC's game-changing SOL8SDR architecture and offering a full 2x100mW of output power, BluCore OEM provides access to a wide range of IP Mesh and unidirectional COFDM waveforms, including DTC's latest MeshUltra. With two USB interfaces capable of supporting USB cameras and headsets as well as Wi-Fi, cellular and Ethernet dongles, BluCore can also be connected to a range of host devices using RNDIS "Ethernet over USB" connectivity.



Features and Benefits:

- 2x100mW COFDM transceivers
- Growing USB support for peripherals such as 3G/4G/Wi-Fi dongles
- 128GB built-in storage
- RNDIS support for Ethernet over USB
- Compact packaging with ultra-miniature connectors
- Very low power consumption: typically 3W
- Exceptionally small size and weight

Product Information:

Product Includes

CA3897	4-way Molex to 4-way Lemo power cable
CA3827	4-way Lemo to banana plugs power cable
CA3740	5-way JST to USB A socket cable
CA3742	5-way JST to USB micro socket cable

Accessory Options (sold separately)

ANT1-100150	1dBi omni antenna SMA 1.0-1.5GHz
ANT2SMA-200250	2dBi omni antenna SMA 2.0-2.5GHz
CA3903	SMA jack to MMCX plug cable
AP009256	USB A 3.0 Gigabit Ethernet adapter
AP007377	USB A to micro USB B cable
CA3787	4-way Lemo to 7.4V slimline battery
CA3794	8.4V 1.3A battery charger with 4-way Lemo socket
CA3801	4-way Lemo to 12V 2A DC mains adapter
CA3983	5-way JST to USB Ethernet adaptor
SA4525	Heat sink clamp
SOL8SDR-M-CAKIT	Cable accessory kits to aid integration. CAKIT guide available.

SOL8SDR-M

BluCore OEM Software Defined Radio Module

Technical Specification (cont.):

IO

RF COFDM transceiver 1	MMCX (female 50Ω)
RF COFDM transceiver 2	MMCX (female 50Ω)
Power input	Molex 4-way 1.25mm
USB1 control and download	JST 5-way 1mm
USB2 control and download	JST 5-way 1mm
GPIO	JST 6-way 1mm

COFDM Transceivers

Application license	SDRAPP-MESH, SDRAPP-TX, SDRAPP-RX
Power	100mW (+20dBm) per output, 200mW total
Power step	0.25dB incremental control
Tuning step	125kHz

Power

DC input	6V to 18V reverse polarity protected
Typical power consumption	3W (excluding camera)

Storage

Medium	Internal microSD 128GB
--------	------------------------

Physical

Dimensions (120170/*167235)	54mm x 55mm x 11mm
Weight (120170/*167235)	62g approx.
Dimensions (210250)	54mm x 50mm x 11mm
Weight (210250)	60g approx.

Environment

Temperature range	-20°C to +50°C with additional cooling
Humidity	Less than 85% non-condensing

Frequency

120170	1.20-1.70GHz
*167235	1.67-2.35GHz
210250	2.10-2.50GHz

Software License Code

#SDRAPP-MESH	IP Mesh
#SDRAPP-IAS	Interference Avoidance Scheme for Mesh
#SDRAPP-L2BRIDGE	Transparent Layer 2 Bridging Mode for Mesh
#SDRAPP-TX	COFDM Transmitter
#SDRAPP-RX	COFDM Receiver
SDRAPP-IPX	IP Encapsulation for COFDM
SDRAPP-GOLD	Gold-TX, Gold-RX, MESH, IAS, IPX
SDRAPP-PLATINUM	Platinum-TX, Platinum-RX, MESH, IAS, IPX
AES128TX	AES 128-Bit Encryption
AES256TX	AES 256-Bit and AES 128-Bit Encryption

* Future development

Refer to separate datasheets for SDRAPP requirements

Export of encrypted products is subject to regulatory export controls.

For further information contact your Sales Account Manager, one of our Regional Sales Offices, or email solent.enquiries@domotactical.com

DTC – Herndon (Headquarters)
2303 Dulles Station Boulevard
Suite 205
Herndon, VA
20171, USA

T: +1 800 665 4648

DTC – Tampa
3845 Gateway Centre Boulevard
Suite 360
Pinellas Park, FL
33782, USA

T: +1 727 471 6900

DTC – Solent
Fusion 2, 1100 Parkway
Solent Business Park
Whiteley, Hampshire
PO15 7AB, UK

T: +44 1489 566 750

DTC – Randers
Haraldsvej 64B
DK-8960
Randers SØ
Denmark

T: +45 8791 8100

DTC – Singapore
21 Media Circle
Infinite Studios #05-06
Singapore
138562

T: +65 6339 0508